



CONVERSION DE GRAMOS A MILILITROS

RELACION DE MEZCLA SEGÚN FICHA TECNICA



ELAST-O-ACTIF

GRS.	ML
9.8	10
19.5	20
29.3	30
39.0	40
48.8	50
58.5	60
68.3	70
78.0	80
87.8	90
97.5	100
146.3	150
195.0	200
243.8	250
292.5	300
341.3	350
390.0	400
438.8	450
487.5	500



AUTOSURFACIER FLEX

GRS.	ML
10.1	10
20.2	20
30.3	30
40.4	40
50.5	50
60.6	60
70.7	70
80.8	80
90.9	90
101.0	100
151.5	150
202.0	200
252.5	250
303.0	300
353.5	350
404.0	400
454.5	450
505.0	500



ANTI-SILICON

GRS.	ML
8.3	10
16.6	20
24.9	30
33.2	40
41.5	50
49.8	60
58.1	70
66.4	80
74.7	90
83.0	100
124.5	150
166.0	200
207.5	250
249.0	300
290.5	350
332.0	400
373.5	450
415.0	500

Nota: Sera importante la exactitud de peso en cada uno de los componentes Producto para mezclar de acuaerdo a ficha tecnica

Transparente/Primer + Aditivo

