


# UTECH U 350 Single Stage

Mezcla	Utech U350 Single Stage		Utech U350 Endurecedor		Super Acelerador 998	
	ML	GMS	ML	GMS	ML	GMS
10	7.5	8.3	2.5	2.5	0.15	0.15
20	15.0	16.5	5.0	5.0	0.30	0.30
30	22.5	24.8	7.5	7.5	0.44	0.44
40	30.0	33.0	10.0	10.0	0.59	0.59
50	37.5	41.3	12.5	12.5	0.74	0.74
60	45.0	49.5	15.0	15.0	0.89	0.89
70	52.5	57.8	17.5	17.5	1.04	1.04
80	60.0	66.0	20.0	20.0	1.18	1.18
90	67.5	74.3	22.5	22.5	1.33	1.33
100	75.0	82.5	25.0	25.0	1.48	1.48
120	90.0	99.0	30.0	30.0	1.77	1.77
140	105.0	115.5	35.0	35.0	2.07	2.07
160	120.0	132.0	40.0	40.0	2.37	2.37
180	135.0	148.5	45.0	45.0	2.66	2.66
200	150.0	165.0	50.0	50.0	2.96	2.96
250	187.5	206.3	62.5	62.5	3.70	3.70
300	225.0	247.5	75.0	75.0	4.44	4.44
350	262.5	288.8	87.5	87.5	5.18	5.18
400	300.0	330.0	100.0	100.0	5.92	5.92
450	337.5	371.3	112.5	112.5	6.66	6.66
500	375.0	412.5	125.0	125.0	7.40	7.40
550	412.5	453.8	137.5	137.5	8.13	8.13
600	450.0	495.0	150.0	150.0	8.87	8.87
650	487.5	536.3	162.5	162.5	9.61	9.61
700	525.0	577.5	175.0	175.0	10.35	10.35
750	562.5	618.8	187.5	187.5	11.09	11.09
800	600.0	660.0	200.0	200.0	11.83	11.83
900	675.0	742.5	225.0	225.0	13.31	13.31
1000	750.0	825.0	250.0	250.0	14.79	14.79



3 Partes de Utech 350 Color de Una Etapa  
1 Partes de Utech U350 Hardener



## DEPARTAMENTO TÉCNICO



Utilizar protección respiratoria adecuada

Nota: Sera importante la exactitud de peso en cada uno de los componentes  
Recuerde mezclar al adicionar cada producto



CEMSA  
Recubrimientos



@CEMSA



Teléfonos:  
35368988  
35369458